



SSC65TR15GTF

Trench FSII Fast IGBT

➤ Features

V_{CES}	V_{GES}	I_C
650V	$\pm 20V$	30A@25°C
		15A@100°C

➤ Description

- High ruggedness performance.
- 10μs short circuit capability.
- Positive $V_{CE(sat)}$ temperature coefficient.
- High efficiency for motor control.
- Excellent current sharing in parallel operation.
- RoHS compliant.


➤ Applications

- Home appliances
- Motordrives
- General inverter


➤ Ordering Information

Device	Package	Shipping
SSC65TR15GTF	TO-220F-3L	50/Tube


➤ Pin Configuration



TO-220F-3L (Top View)



Pin Configuration



Marking

(XXYY: Internal Traceability Code)



➤ **Absolute Maximum Ratings ($T_{vj}=25^{\circ}\text{C}$ unless otherwise noted)**

Symbol	Parameter		Ratings	Unit
V_{CES}	Collector-Emitter Voltage		650	V
V_{GES}	Gate-Emitter Voltage		± 20	V
I_C	Collector Current	$T_C=25^{\circ}\text{C}$	30	A
		$T_C=100^{\circ}\text{C}$	15	
I_{Cpuls}	Pulsed Collector Current, t_p limited by T_{vjmax}		60	A
P_D	Power Dissipation ^a	$T_C=25^{\circ}\text{C}$	39	W
		$T_C=100^{\circ}\text{C}$	19	
T_J	Operating Junction and Storage Temperature Range		-40~175	$^{\circ}\text{C}$
T_{STG}	Operating Junction and Storage Temperature Range		-55~150	$^{\circ}\text{C}$
t_{sc}	Short circuit withstand time		10	us

➤ **Thermal Resistance Ratings**

Symbol	Parameter	Typ	Max	Unit
$R_{\theta JA}$	Junction-to-Ambient Thermal Resistance		50	$^{\circ}\text{C}/\text{W}$
$R_{\theta JC}$	Thermal Resistance, Junction to Case for IGBT		3.8	
$R_{\theta JC}$	Thermal Resistance, Junction to Case for Diode		4.2	

**➤ Electrical Characteristics of IGBT (T_{vj}=25°C unless otherwise noted)**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
V _{(BR)CES}	Collector-Emitter Breakdown Voltage	V _{GE} = 0V, I _C = 0.25mA	650			V
I _{CES}	Collector-Emitter Leakage Current	V _{GE} =0V, V _{CE} =650V, T _{vj} =25°C			50	uA
I _{GES(F)}	Gate to Emitter Forward Leakage	V _{GE} = +20V, V _{CE} = 0V			100	nA
I _{GES(R)}	Gate to Emitter Reverse Leakage	V _{GE} = -20V, V _{CE} = 0V			-100	nA
V _{CE(sat)}	Collector-Emitter Saturation Voltage	I _C =15A, V _{GE} =15V, T _{vj} =25°C		1.6		V
		I _C =15A, V _{GE} =15V, T _{vj} =150°C		1.9		V
V _{GE(th)}	Gate Threshold Voltage	I _C = 1mA, V _{CE} = V _{GE}	5.4	5.6	5.9	V
C _{ies}	Input Capacitance	V _{CE} = 30V, V _{GE} = 0V, f = 1MHz		1055		pF
C _{oes}	Output Capacitance			57		
C _{res}	Reverse Transfer Capacitance			15		
T _{D(ON)}	Turn-on delay time	T _{vj} =25°C, V _{CC} =400V, I _C =15A, V _{GE} =0/15V, R _g =10Ω, Inductive Load		17		ns
T _r	Rise time			14		
T _{D(OFF)}	Turn-off delay time			104		
T _f	Fall time			46		
E _{on}	Turn-On Switching Loss			0.30		mJ
E _{off}	Turn-Off Switching Loss			0.27		
E _{ts}	Total Switching Loss			0.57		
T _{D(ON)}	Turn-on delay time	T _{vj} =150°C, V _{CC} =400V, I _C =15A, V _{GE} =0/15V, R _g =10Ω, Inductive Load		16		ns
T _r	Rise time			15		
T _{D(OFF)}	Turn-off delay time			119		
T _f	Fall time			81		
E _{on}	Turn-On Switching Loss			0.38		mJ
E _{off}	Turn-Off Switching Loss			0.4		
E _{ts}	Total Switching Loss			0.78		
Q _G	Total Gate Charge	V _{CC} = 520V, I _C = 15A, V _{GE} = 0/15V		55		nC



➤ **Electrical Characteristics of Diode ($T_{vj}=25^{\circ}\text{C}$ unless otherwise noted)**

Symbol	Parameter	Test Conditions	Min.	Typ.	Max.	Unit
VF	Diode forward voltage	IF=15A, $T_{vj}=25^{\circ}\text{C}$		1.4		V
		IF=15A, $T_{vj}=150^{\circ}\text{C}$		1.2		V
Trr	Diode reverse recovery time	VR=400V IF=15A diF/dt=600A/ μs $T_{vj}=25^{\circ}\text{C}$		55		ns
Irrm	Diode peak reverse recovery current			9.5		A
Qrr	Diode reverse recovery charge			220		nC
Trr	Diode reverse recovery time	VR=400V IF=15A diF/dt=600A/ μs $T_{vj}=150^{\circ}\text{C}$		75		ns
Irrm	Diode peak reverse recovery current			15		A
Qrr	Diode reverse recovery charge			450		nC

➤ **Typical Performance Characteristics ($T_{vj}=25^{\circ}\text{C}$ unless otherwise noted)**




Fig 1. Typical output characteristic ($T_{vj}=25^{\circ}\text{C}$)




Fig 2. Typical output characteristic ($T_{vj}=175^{\circ}\text{C}$)




Fig 3. Power dissipation as a function of T_c





Fig 4. Typical I_F as a function of V_F



**Fig 5. Typical $V_{GE(th)}$ as a function of T_{vj}
($I_C=1\text{mA}$)**






Fig 6. Typical V_F as a function of T_{vj}

➤ **Typical Performance Characteristics ($T_{vj}=25^{\circ}\text{C}$ unless otherwise noted)**




➤ Typical Performance Characteristics ($T_{vj}=25^{\circ}\text{C}$ unless otherwise noted)



➤ Package Information

TO220F



Symbol	MILL IMETER		
	Min	Nom	Max
A1	2.34	2.54	2.74
A2	4.5	4.7	4.9
A3	2.56	2.76	2.96
b1	0.7	0.8	0.9
b2	1.23	1.3	1.47
c	0.45	0.5	0.6
D	9.96	10.16	10.36
E	28.35	28.85	29.35
E1	15.67	15.87	16.07
e	2.54REF		
L1	6.48	6.68	6.88
L2	3.2	3.3	3.4
L3	12.68	12.98	13.28
øP	3.03	3.4	3.5



DISCLAIMER

SSCSEMI RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. SSCSEMI DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENCE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

THE GRAPHS PROVIDED IN THIS DOCUMENT ARE STATISTICAL SUMMARIES BASED ON A LIMITED NUMBER OF SAMPLES AND ARE PROVIDED FOR INFORMATIONAL PURPOSE ONLY. THE PERFORMANCE CHARACTERISTICS LISTED IN THEM ARE NOT TESTED OR GUARANTEED. IN SOME GRAPHS, THE DATA PRESENTED MAY BE OUTSIDE THE SPECIFIED OPERATING RANGE (E.G. OUTSIDE SPECIFIED POWER SUPPLY RANGE) AND THEREFORE OUTSIDE THE WARRANTED RANGE.

OUR PRODUCT SPECIFICATIONS ARE ONLY VALID IF OBTAINED THROUGH THE COMPANY'S OFFICIAL WEBSITE, CRM SYSTEM, OR OUR SALES PERSONNEL CHANNELS. IF CHANGES OR SPECIAL VERSIONS ARE INVOLVED, THEY MUST BE STAMPED WITH A QUALITY SEAL AND MARKED WITH A SPECIAL VERSION NUMBER TO BE VALID.